

Nikon NE-102 and NE-103 Theodolites



Datasheet



Nikon Quality You Can Trust

Key Features

- 5" angle accuracies
 - Compensator on NE-103
- Large display and keyboard
- Alkaline (standard AA) batteries with battery life indicator
- IPX6 waterproofing
- Illuminated display and telescope
- Superior Nikon optics

Nikon NE-102 and NE-103 Engineering Theodolites

The construction engineering industry demands stable products that hold their calibration and provide reliable and accurate long-term performance. Using Nikon engineering theodolites, engineering contractors and surveyors are assured a high level of control and durability through many years of hard use.

The ergonomic keypad and display provide easy access to the powerful and accurate measurement capabilities of the Nikon NE-102 and NE-103 theodolites. Large, easy-to-identify buttons provide one-button operation for key functions. A large text display area makes information easy to read and use on the job. This design provides for a very short learning curve and utilization within a matter of minutes.

Nikon Engineering Theodolites - Aligning Strength and Accuracy

The Nikon NE-102 and NE-103 engineering theodolites are an ideal choice for a wide range of construction engineering alignment applications, including alignment control, tilt-up walls, curtain walling and steel column erection. And, with an IPX6 waterproof rating, these ruggedly designed instruments maintain their performance year after year, even in the harshest of jobsite conditions.

Nikon engineering theodolites are precise, reliable and rugged.

Nikon NE-102 and NE-103 Theodolites

NE -102

NE -103

Angle Measurement

Reading system	photoelectric incremental encoder	photoelectric incremental encoder
Circle diameter	79 mm (3.1 in)	79 mm (3.1 in)
Unit of reading	degree/gon/mil	degree/gon/mil
Minimum digital reading	5/10", 1/2 mgon, 0.02/0.05 mil	5/10", 1/2 mgon, 0.02/0.05 mil
Accuracy (DIN 18723)	5"/1 mgon	5"/1 mgon

Telescope

Effective diameter of objective	45 mm (1.8 in)	45 mm (1.8 in)
Magnification	30x	30x
Image	erect	erect
Field of view (at 100m/100ft)	1°20' (2.3 m/2.3 ft)	1°20' (2.3 m/2.3 ft)
Minimum focusing distance	0.7 m (2.3 ft)	0.7 m (2.3 ft)
Stadia multiplier constant	100	100
Stadia additive constant	0	0
Reticle illuminator	Yes	Yes

Automatic Vertical Compensator

Type	-	liquid-electric detection
Working range	-	±3' (out-of-range warning provided)

Display / Keypad

Front		
Type	dot-matrix LCD (20 characters x 2 lines)	dot-matrix LCD (20 characters x 2 lines)
Backlight	1-level illumination	1-level illumination
Keypad	5 buttons	5 buttons
Rear		
Type	dot-matrix LCD (20 characters x 2 lines)	dot-matrix LCD (20 characters x 2 lines)
Backlight	1-level illumination	1-level illumination
Keypad	5 buttons	5 buttons

Optical Plummet

Magnification	3x	3x
Field of view	5°	5°
Focus range	0.5 m (1.6 ft) to infinity	0.5 m (1.6 ft) to infinity

Level Sensitivity

Plate level	30"/2 mm	30"/2 mm
Circular level	10"/2 mm	10"/2 mm

Leveling Base

Type	detachable	detachable
------	------------	------------

Ambient Temperature Range

-20 to 50 C (-4 TO 122 °F)	-20 to 50 C (-4 TO 122 °F)
----------------------------	----------------------------

Environmental Rating

IP56	IP56
------	------

Dimensions

Instrument	153.5 x 172 x 334 mm (6.0 x 6.8 x 13.1 in)	153.5 x 172 x 334 mm (6.0 x 6.8 x 13.1 in)
------------	--	--

Weight

Instrument	4.5 kg (9.9 lb)	4.6 kg (10.1 lb)
Carrying case	3.9 kg (8.6 lb)	2.5 kg (5.4 lb)

Power Supply

Battery type	1.5 V AA x 6	1.5 V AA x 6
Continuous operating time (at 68 °F/20 °C)	48 hours	48 hours



PRECISE • RELIABLE • RUGGED

Contact Information:

AMERICAS

Spectra Precision Division
10368 Westmoor Drive
Westminster, CO 80021, USA
+1-720-587-4700 Phone
888-477-7516 (Toll Free in USA)

EUROPE, MIDDLE EAST AND AFRICA

Spectra Precision Division
Rue Thomas Edison
ZAC de la Fleuriaye - CS 60433
44474 Carquefou (Nantes), France
+33 (0)2 28 09 38 00 Phone

ASIA-PACIFIC

Spectra Precision Division
80 Marine Parade Road
#22-06, Parkway Parade
Singapore 449269, Singapore
+65-6348-2212 Phone



www.spectraprecision.com

Specifications subject to change without notice.

©2015, Trimble Navigation Limited. All rights reserved. Nikon is a registered trademark of Nikon Corporation. All other trademarks are the property of their respective owners. (2015/08)